

# Fiber coupler and collimator

18-00981



## Features and Advantages


Precision etched microlens array for fiber optic collimation and refocusing applications. Low pointing error and minimal optical phase front distortions enabled by wafer-level manufacturing.

\* Product picture & drawing only for reference.

## Product Specifications

Specification Data	Unit	Value
Material		Silicon
Length (L)	mm	7.45 ± 0.05
Width (W)	mm	2.2 ± 0.05
Center thickness (T)	mm	0.5 ± 0.01
Optical effective area	mm	φ0.620
Lens radius of curvature	mm	3.378
ROC tolerance within lens array	%	3
ROC tolerance between parts	%	3
Conic constant		0
Pitch (P)	mm	0.750
Design wavelength	nm	1310
Transmission (with coating)	%	>98
Reflectivity	%	<0.5
Effective focal length (EFL)	mm	1.350
Working distance (WD)	mm	1.202
<b>Product description</b>		<b>Si_Sph_1x8_P0.75_R3.378_t0.5_1_001</b>

## Product Drawing (mm)



Rev 01 | Updated March 28, 2024

1

All rights reserved. Product specifications and descriptions are subject to change. All our products are patent pending. Please contact our sales representatives for complete details.

Focuslight Switzerland SA

Address: Rouges-Terres 61, 2068 Hauterive, Switzerland

Focuslight (DG) Microoptics Co. Ltd.

Address: No. 49, Jingyi Road, Dongcheng Street, Dongguan City, Guangdong Province, China

Tel: +41 32 566 44 44 (CH) +86 29 8956 0050 (CN) | Email: sales@focuslight.com | Website: <https://www.focuslight.com>